



HELIX Speedster

The HELIX Speedster, with its new revolutionary synthetic stock strikes out in a new direction as a hunting rifle. The top-opened OmegaGrip combines two classic stock principles into an ergonomic and fast novelty. Because the good ergonomics during the shot of classic thumbhole stock constructs only reveals its disadvantages when reloading: During fast bolt action, the threading in and out of the thumb into the hole is obstructive.

The new SpeedStock of the HELIX Speedster eliminates this problem. The thumb slides as if on rails along the ergonomic stock shape into shooting position on the OmegaGrip as well as out of it when reloading. The automatically adjustable stock comb can be adjusted in its height at the push of a button, an important advantage for shooting with a scope.

TECHNICAL DATA



SYSTEM

Straight-pull bolt-action rifle with a 1:2 transmission / closed system housing / real take-down / Barrel change option / 6 locking slugs turning head lock / Manual cocking lever / 3-round magazine (+1)

CALIBRE

Mini calibre: .222 Rem. / .223 Rem. /
Standard calibre: .243 Win. / .270 Win. / 6,5x55SE / 7x64 / .308 Win. / .30-06 Spring. / 8x57IS / 9,3x62 /
Magnum calibre: .300 Win. Mag. / .338 Win. Mag. / 7mm Rem. Mag.

TRIGGER

Direct trigger adjustable from approx. 900 to 1.900 gramms / **Optional:** TAR-GT trigger smoothly adjustable from approx. 500 to 1500 gramms / gold plated trigger

WEIGHT

approx. 3,2 kg (at 56cm barrel length)

LENGTH Overall length 107 cm (at 56 cm barrel length)

BARREL Standard barrel (Ø 17 mm) / i-Sight system /
Optional: Semi-weight barrel (Ø 19 mm) / Fluted barrel

		BARREL DIAMETER 17 mm					
BARREL LENGTH ▶		510 mm		560 mm		610 mm	
DETACHABLE SIGHTS ▶		with		with		with	
MUZZLE THREAD M15x1 ▶		with		with		with	
GEOMETRY ▶		round	fluted	round	fluted	round	fluted
MINI	.222 Rem.			●	○		
	.223 Rem.			●	○		
STANDARD	.243 Win.			●	○		
	.270 Win.			●	○		
	7x64			●	○		
	.308 Win.	○	○	●	○		
	.30-06 Spring.	○	○	●	○		
	8x57IS	○	○	●	○		
	9,3x62	○	○	●	○		
MAGNUM	7 mm Rem.Mag.					●	○
	.300 Win.Mag.					●	○

● standard ○ optional

		BARREL DIAMETER 19 mm						
BARREL LENGTH ▶		470 mm	510 mm		560 mm		610 mm	
DETACHABLE SIGHTS ▶		with	with		with		with	
MUZZLE THREAD M15x1 ▶		with	with		with		with	
GEOMETRY ▶		round	round	fluted	round	fluted	round	fluted
MINI	.222 Rem.				○	○		
	.223 Rem.				○	○		
STANDARD	.243 Win.	▲ ○			○	○		
	.270 Win.	▲ ○			○	○		
	7x64	▲ ○			○	○		
	.308 Win.	▲ ○	○	○	○	○		
	.30-06 Spring.	▲ ○	○	○	○	○		
	8x57IS	▲ ○	○	○	○	○		
	9,3x62	▲ ○	○	○	○	○		
MAGNUM	7 mm Rem.Mag.						○	○
	.300 Win.Mag.						○	○
	.338 Win.Mag.						●	○

● standard ○ optional ▲ standard for the Helix Tracker and Helix Suppressor

STOCK

SpeedStock with Soft-Touch inlays / height-adjustable stock comb with MemoryCheek-Piece function / without tools exchangeable butt plates (in different lengths) / Boresnake integrated into the pistol grip / Slim QD sling swivels / **Synthetic-colours:** green with black Soft-Touch Inlays

ENGRAVINGS

none / black system casing

MOUNTS

integrated Picatinny profile as mounting basis /
Optional: Mounting basis Weaver rail / Kiliic mounts

OPTIONS

5-round magazine (+1) / Muzzle break / Merkel Suppressor / Stock key / Harris bipod
